

The MT-300 Bracelet Beacon B4 has built-in BLE iBeacon technology and has a kid's friendly elephant design. It is a smart bracelet to prevent children from going missing.

You can monitor your child and get an alert when your child wanders away, so MT-300 smart bracelet makes sure you never lose sight of your child, even at the beach or in an amusement park.

### **FEATURES**

- Programmed MiniBeacon standard firmware
- Included 1pc CR2016 coin battery
- The max. 30 meters advertising distance
- Ultra-low power consumption chipset nRF51822 with ARM core
- Easy to print the logo on the center of top case;

## CERTIFICATIONS

- iBeacon MFi License
- FCC Regulation (FCC Part 15.)
- CE Regulations

# SPECIFICATIONS

### Compatibility

- Supported iOS 7.0+ and Android 4.3+ system;
- Compatible with Apple iBeacon<sup>TM</sup> standard;
- Compatible with all Bluetooth 4.0 (BLE) devices;

### Long Battery Lifetime and Battery Level

- 3 months, with the default settings;
- Easy to get the real-time battery level notification;

### Soft-reboot

- Reboot the device via command without any tools;

### **Connection Mode**

- Advertising mode, non-connectable;
- Configuration mode, connectable;

### Waterproof

- IP67 Level;

## **Configurable Parameters**

- UUID, Major, Minor, Device Name, Password etc.
- Special Configuration APP;

### **Transmission Power Levels**

- 8 adjustable levels, range from 0 to 7
- Transmission power range: -30dBm to +4dBm;

### Security

- 8 characters password (Lock/Unlock parameters);
- Broadcast the encrypted data if needed;
- AES HW encryptio



MT-300 Bracelet Beacon Image 1



### **OPERATION**

Turn On: Please press the center of bracelet and keep on holding 5 seconds (you will hear a "b" sound), the LED will light on 5 seconds then off.

Turn Off: Please press the center of bracelet and keep on holding 5 seconds (you will hear a "b" sound), the LED will flash 5 times then off.



## **ELECTRONIC PARAMETERS**

ltem	Value	Remarks
Case Color	Blue	Other colors can be customized
Battery Model	1 x CR2016	1pc CR2016 coin battery, 85mAh, 3.0V
Operation Voltage	1.8-3.6V	DC
Transmission Circuit	10.5mA (Max.)	Tested at 0dBm transmission power
Transmission Range	30 meters	Maximum
Antenna	50ohm	On board / PCB Antenna
Accessories	Double adhesive	1pc, high-strength, 3M brand;
Net Weight	19.0g	With battery but without package
Size	201 x 32.4 x 11.5 mm	Null

### PACKING INFORMATION

Details	Package Box	Carton
Quantity (B4)	16pcs per package box	160pcs per carton
Net Weight	0.31kg	3.1Kg
Gross Weight	0.38Kg	5.0Kg
Size	30.5 x 11 x 7.5 cm	32 x 23 x 40 cm

### DECLARATION

The contents of this datasheet are subject to change without prior notice for further improvement.

Mobitron is a registered trademark of Mobitron Inc., in Canada, U.S.A. and/ or other countries. All other brand names, products, or trademarks belong to their respective holders. Mobitron reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document. © 2017 Mobitron Inc., All rights reserved.